

HYDRAULIC HAND STACKER



Mast frame is made of high-quality steel which is high strength and long lasting. Special rolling process of "C" type steel frame which makes the welding connection durable and cannot be deformed.

The door frame and the fork are suitable for various venues and the use of the pallet. Explosion proof valve that will block the hydraulic loop to avoid the fork to decline rapidly when stuck at a fixed height effectively protecting the safety of the goods and the user. Manual pedal can replace the operation of the lifting function which improves work efficiency.

Labor-cost saving.

TECHNICAL PARAMETERS

TECHNICAL PARAMETERS						
Product Code	LHHS	1016	1516	2016	1030	1525
Capacity	kg	1000	1500	2000	1000	1500
Load Center	mm	400	400	400	400	400
Type of Lifting	Manual/Foot					
Wheel Type	Nylon					
Minimum Fork Height	mm	90	90	90	90	90
Maximum Fork Height	mm	1600	1600	1600	3000	2500
Fork Length	mm	1150	1150	1150	1150	1150
Single Fork Size	mm	1150x150x60	1150x150x60	1150x160x60	1150x150x60	1150x150x60
Overall Height	mm	1985	2085	2085	2080	1880
Minimum Turning Radius	mm	1400	1400	1400	1400	1400
Approximate Weight	kg	220	250	275	320	320